



Product : ACRYLINDO 1701-75
MSDS Number : CMSD-078
Version Date : November 25, 2010

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product : ACRYLINDO 1701-75
Type : Copolymer Acrylic Resin

Supplier details:

PT ALKINDO MITRARAYA (AMR)
JI Gatot Subroto km. 8, Desa Kadu Jaya, Kecamatan Curug
Tangerang 15810
INDONESIA
Phone : + 62 – 21 – 59302250 (hunting 10 lines)
Facsimile : + 62 – 21 – 59302251
Email : alkindo@alkindo.net
Website : www.alkindo.net

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION

Flammable Liquid Hazard Category 3
Acute Toxicity (Dermal) Hazard Category 4
Acute Toxicity (Inhalation) Hazard Category 4
Chronic Aquatic Hazard Category 4
Skin Corrosion / Irritation Hazard Category 2
Serious Eye Damage / Eye Irritation Hazard Category 2A
Carcinogenicity Hazard Category 2
Target Organ Systemic Toxicant (TOST) - Single Exposure Hazard Category 3
Toxic To Reproduction Hazard Category 2

GHS LABELING



GHS SIGNAL WORD

Danger

HAZARD STATEMENTS

Flammable liquid and vapour
Suspected of causing cancer
Suspected of damaging fertility or the unborn child
Harmful in contact with skin
Harmful if inhaled
Causes skin irritation
Causes serious eye irritation
May cause drowsiness and dizziness



Product : ACRYLINDO 1701-75
MSDS Number : CMSD-078
Version Date : November 25, 2010

Page 2 of 6

PRECAUTIONARY STATEMENTS

Prevention

Keep away from heat, sparks and open flame. - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and other equipment. Use only nonsparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing vapors or spray mist. Wear protective gloves/clothing and eye/face protection.

Response

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTRE or doctor/physician if you feel unwell. Specific measures - refer to supplemental first aid instructions. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell. Specific treatment - refer to supplemental first aid instructions. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. In case of fire, use the following media for extinction: water spray or fog, alcohol foam, carbon dioxide, dry chemical.

Storage

Store in well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.

Disposal

Dispose of contents/container in accordance with local and national regulations.

3. COMPOSITION INFORMATION

CHEMICAL DESCRIPTION

Acrylic polyol resin, in solution in xylene/butyl acetate/arcosolve PMA.

HAZARDOUS COMPONENTS

Propylene Glycol Methyl Ether Acetate	24 - 26 %
CAS No. 108-65-6	

4. FIRST AID MEASURES

INGESTION:

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

SKIN CONTACT:

Remove contaminated clothing and shoes without delay. Wash immediately with plenty of water. Do not reuse contaminated clothing without laundering. Get medical attention if pain or irritation persists after washing or if signs and symptoms of overexposure appear.

EYE CONTACT:

Rinse immediately with plenty of water for at least 15 minutes. Obtain medical advice if there are persistent symptoms.

INHALATION:

Remove to fresh air. If breathing is difficult, give oxygen. Obtain medical advice if there are persistent symptoms.



Product : ACRYLINDO 1701-75
MSDS Number : CMSD-078
Version Date : November 25, 2010

Page 3 of 6

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:

Foam, dry powder, carbon dioxide, water spray.

EXPOSURE HAZARDS:

Keep containers cool by spraying with water if exposed to fire. Heating will cause pressure rise with risk of bursting and subsequent explosion. For decomposition products see Section 10.

PROTECTIVE EQUIPMENT:

Fire fighters and others exposed, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:

Use personal protection recommended in Section 8. Avoid breathing vapor from hot material.

ENVIRONMENTAL PRECAUTIONS:

Do not allow to enter drains and water courses. If sewers become contaminated contact Local Water Authority and Police. Should resin enter other waterways inform the Environment Agency.

METHODS FOR CLEANING UP:

Absorb onto sand. Drums leaking near base may be inverted. For disposal see Section 13.

7. HANDLING & STORAGE

HANDLING:

Handle in a well-ventilated area. Keep concentration of vapors as low as is reasonably practicable and observe occupational exposure limits detailed in Section 8.

STORAGE:

Store in closed containers away from sources of heat in a well-ventilated flameproof area. Storage temperature: 25 -30°C.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING MEASURES:

Ensure adequate ventilation to keep vapor concentrations below occupational exposure limits.

OCCUPATIONAL EXPOSURE LIMITS (EH40):

Arcosolve PMA

100 ppm

EYES:

Goggles.

RESPIRATORY PROTECTION:

Wear suitable respiratory protection if exposure limits may be exceeded. Airline respirator or cartridge respirator with appropriate filter.

HAND PROTECTION:

Wear impermeable gloves.

SKIN PROTECTION:

Wear suitable protective clothing.



Product : ACRYLINDO 1701-75
MSDS Number : CMSD-078
Version Date : November 25, 2010

Page 4 of 6

9. PHYSICAL & CHEMICAL PROPERTIES

Phase : Liquid (25.0 °C)
Appearance, Color : Transparent
Odor : Thinner / Solvent – like
Boiling point (760 mmHg) : 140 - 150°C
Water solubility : insoluble
Flash point (°C) : 47.0 (Tag close cup)

10. STABILITY & REACTIVITY

CONDITIONS TO AVOID:

Heating will cause pressure rise with risk of bursting and subsequent explosion.

HAZARDOUS DECOMPOSITION PRODUCTS:

Thermal decomposition products may include carbon monoxide and carbon dioxide.

11. TOXICOLOGICAL INFORMATION

LABORATORY DATA:

Copolymer acrylic resin

This product has not been tested for toxicity. It is classified as sensitizing under 88/379/EEC and subsequent amendments.

HAZARDOUS INGREDIENTS TOXICITY:

Arcosolve PMA

The vapour is irritating to the nose, throat and lungs and may cause coughing, shortness of breath, and dizziness. The liquid is irritating to the eyes and skin and may be absorbed through the skin. Accidental ingestion may cause a little effect.

12. ECOLOGICAL INFORMATION

ASSESSMENT:

If properly handled, this material should not present a serious environmental hazard.

TEST RESULTS:

AMR has not conducted environmental studies on this product. The product does not contain any substance that is classified under EC legislation for environmental effects. Data is available on some of the components.

Arcosolve PMA

BOD5 >0.5 Readily biodegradable

COD

13. DISPOSAL CONSIDERATIONS

METHODS OF DISPOSAL; WASTE OF RESIDUES; CONTAMINATED PACKAGING

Control incineration.

Emptied drums contain solvent vapors, hazardous in respect of fire, explosion and noxiousness.

Disposal only to licensed drum reconditioners.

14. TRANSPORT INFORMATION

Land Transport

Proper Shipping Name : Resin solution
UNDG Class : 3
UN No : 1866
Packing Group : III
Transport label required : Flammable liquid
HAZCHEM Code : 3[Y]



Product : ACRYLINDO 1701-75
MSDS Number : CMSD-078
Version Date : November 25, 2010

Page 5 of 6

Sea Transport (IMO)

Proper Shipping Name : Resin solution
IMDG Class : 3
UN Number : UN1866
Packing Group : III
Transport label required : Flammable liquid

Air Transport (ICAO/IATA)

Proper Shipping Name : Resin solution
Hazard Class : 3
Packing Group : III
UN : UN1866
Transport Label Required : Flammable liquid
Packing Instruction/Maximum Net Quantity Per Package:
Passenger Aircraft : 309; 60L

15. REGULATORY INFORMATION

European Union (EU): All components of this product are included on the European Inventory of Existing Chemical Substances (EINECS) or are not required to be listed on EINECS.

United States (USA): All components of this product are included on the TSCA Chemical Inventory or are not required to be listed on the TSCA Chemical Inventory.

China: All components of this product are included on the Chinese Inventory or are not required to be listed on the Chinese Inventory.

Japan: All components of this product are included on the Japanese (ENCS) Inventory or are not required to be listed on the Japanese Inventory.

RISK PHRASES:

R10 Flammable
R20/21 Harmful by inhalation & in contact with skin
R38 Irritating to skin

SAFETY PHRASES:

S24/25 Avoid contact with skin and eyes
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical Advice.
S37 Wear suitable gloves.
S51 Use only in well ventilated areas.

16. OTHER INFORMATION

Whilst every care has been taken in the preparation of this material safety data sheet, the same has been produced from information and data currently available to PT Alkindo Mitraraya at the date hereof; however, PT Alkindo Mitraraya cannot be responsible for any errors or omissions. If in any doubt, please consult PT Alkindo Mitraraya.

Reasons for issue: New Format