



ACRYLINDO 1772-50

I. DESCRIPTION

ACRYLINDO 1772-50 is a modified cationic acrylic for grinding resin, having good compatibility with long and medium oil alkyd.

II. PROPERTIES

- Excellent wetting
- Good gloss
- Excellent storage stability
- Fast dry but not able to be skinning

III. SUGGESTED USES

- Pigment paste for point of sales DIY synthetic enamels

IV. TYPICAL PROPERTIES

- Resin type : Cationic modified acrylic
- Solvent : Methoxy propyl acetate
Xylene
- Tg (°C) : 38

V. SPECIFICATION

- NV (%) : 50 ± 1
- Viscosity (G-H, 25°C) : max. C
- AV solution (mg KOH/g) : max. 1
- Color (Gardner) : max. 2
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic hydrocarbon : not dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.